

## Description

High-performance high-pressure gear oil made from carefully selected base oils and multifunctional additives for vehicles with tried and tested transmission technology. Provides a stable lubricating film and minimizes wear. Provides extremely good lubrication properties and outstanding corrosion protection. Enables smoother gearshifting.

## Properties

- reduces running noise
- high pressure-absorption capability
- minimizes wear
- does not attack common sealing materials
- excellent viscosity/temperature properties
- excellent resistance to aging

## Specifications / Approvals

API GL4 • MB-Approval 235.1 • MIL-L 2105 • ZF TE-ML 17A • ZF approval number ZF000694

Nordsen recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

MAN 341 Typ E1 • MAN 341 Typ Z2

## Technical data

SAE class (gear oils)	80W SAE J306
Density at 15 °C	0,88 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	93,4 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	11,4 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -26 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	110 DIN ISO 2909
Pour point	-27 °C DIN ISO 3016
Flash point	218 °C DIN ISO 2592
Color number (ASTM)	3,5 DIN ISO 2049

## Areas of application

For transmissions (particularly manual transmissions) and axle drives with normal to high load for which an API GL4 gear oil is required.



## Application

When choosing, keep to the viscosity class stipulated by the transmission manufacturer. Mixable with all branded gear oils. Full effectiveness only when used unmixed.

## Available pack sizes

500 ml Can plastic	1401 DE-EN-ES-IT-PT
1 l Can plastic	1020 DE-EN-ES-IT-PT
20 l Canister plastic	1033 DE-EN-ES-IT-PT
60 l Black plate barrel	1039 DE-EN
205 l Black plate barrel	4718 DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

